

# DECLARATION OF PERFORMANCE

DE0102/02

**PCI**<sup>®</sup>

Für Bau-Profis

Augsburg, 19.01.2015

Unique identification code of the product-type:

**PCI Seccoral® 2K Rapid (DE0102/02)**

Intended use/es:

**EN 14891 CM 01P**

**Liquid-applied water impermeable product for installations beneath ceramic tiling  
(bonded with PCI C2, C2F or R2 adhesives in accordance with EN 12004)**

Manufacturer:

**PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg**

System/s of AVCP:

**System 3**

Harmonised standard / Notified body/ies:

**EN 14891:2012 + AC:2012**

**MATERIALPRÜFANSTALT FÜR DAS BAUWESEN BRAUNSCHWEIG (NB 0761)**

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	≥ 0,5 MPa	System 3	EN 14891:2012 + AC:2012
Tensile adhesion strength after water contact	≥ 0,5 MPa		
Tensile adhesion strength after heat ageing	≥ 0,5 MPa		
Tensile adhesion strength after contact with lime water	≥ 0,5 MPa		
Crack bridging ability at low temperature	≥ 0,75 mm at -5°C		
Waterproofing	No penetration		
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 MPa		
Dangerous substances	Comply with 4.2 (EN 14891)		

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....  
Clemens Bierig  
managing director



.....  
Manfred Grundmann  
managing director