

Multi-use fixative

UFX 382

Fields of application


- For floors in the interior.
- Acrylic resin dispersion as fixative for
 - CV and textile floorings with different backings, also for synthetic double backing, PUR foam backing and non woven backing,
 - natural rubber coverings.
- Suitable for wear surfaces such as PVC, linoleum or sealed parquet.
- Suitable for
 - underfloor heating
 - exposure to chair castors in residential areas.
- Suitable for the use on ships, meets the requirements of Marine Equipment Directive (MED) 96/98/EC.

Features and benefits


- Very low emission, GEV-EMICODE EC 1.
- Awarded the environmental label "Blauer Engel" due to low emission (RAL UZ 113).
- Solvent-free to TRGS 610; Giscode D 1.
- Flooring can be removed.

Packaging size

- 12 kg plastic pail stock no. 4370/7
- 3 kg plastic pail stock no. 4371/4



0098-11



Emissionsgeprüftes Bauprodukt nach DIBt-Grundsätzen



A brand of

BASF
The Chemical Company

Technical data

Material

Material base	acrylate dispersion, mineral fillers, additives, preservative agents
Components	single-component
Consistency	fluid
Colour	white
Labelling to	
- Carriage of Dangerous Goods by Road, Rail and Inland Waterways	non hazardous
- Regulation for hazardous substances	no labelling requirement for this product
<i>For further information see Health and Safety.</i>	
Shelf life	min. 9 months when stored in dry conditions and protected from frost, no permanent storage over +30 °C

Application

Consumption	approx. 100 to 200 g/m ²
Ambient and substrate temperature	+ 15 °C to + 25 °C
Application method	one-sided application to the substrate, fine-pored foam roller or TKB** notch size A 1 (see figure) depending on backing
Evaporation time* for	
- textile floorings	approx. 10 to 15 minutes
- CV floorings	approx. 20 to 30 minutes
- natural rubber coverings	approx. 20 to 30 minutes
Able to bear weight after*	immediately

* At +23 °C and 50% relative humidity. Higher temperatures reduce, lower temperatures increase the times given. Higher humidity increases the times given.

** Technische Kommission Bauklebstoffe (German technical commission for construction adhesives)



notch size A 1

Suitable substrates

- Primed absorbent mineral floors.
- Primed mineral PCI levelling compounds.
- Primed chipboards.
- Non absorbent substrates, also firmly bonding wear surfaces such as PVC, linoleum or sealed parquet.

Preparation of substrate

- The requirements in accordance with the German standard DIN 18 365 apply.
- The substrate must be prepared for subsequent coverings, clean, dry, structurally sound, level and able to bear weight, free from cracks, old paint and other residues which could impair adhesion. The substrate must also be free from any sand layer.
- Wear surfaces must firmly bond to the substrate and thoroughly cleaned before applying UFX 382.
- Smoothed substrates, chipboards and other absorbent substrates must be primed with VG 2 multi-use primer or VG 1 S dispersion primer before applying UFX 382. The primer prevents too much water from penetrating into the substrate when later removing the fixative by washing.

Application procedure of UFX 382

- Cut covering to size, lay down in the room and fold back by half. Apply UFX 382 to the substrate evenly and ensure good adhesive transfer to the backing of the covering. Install covering after an evaporation time of approx. 10 to 30 minutes. The film should be dry but still tacky (check with your fingertip).
- **Removal of floorings:**
Loosen flooring at an edge and take off. Moistened residues of the fixative with suitable cleaning agents and remove mechanically after approx. 30 minutes.
Wear surfaces should then be cleaned professionally.
- Clean tools with water immediately after use. Clean contaminated coverings promptly with water or carpet cleaner (textile coverings).
- **Follow the special installation instructions issued by the flooring manufacturers.**

Please note

- Please contact the Technical help-line for the use in commercial and industrial areas.
- Wear surfaces might look different after the fixative has been removed - depending on the fixed secondary backing.

Health and Safety

Keep out of reach of children. Ensure sufficient ventilation during the application and drying phase. Avoid eating, drinking and smoking during the

application of the product. In case of contact with eyes or skin, rinse immediately with plenty of water. Product contains isothiazolinone.

For further information refer to the PCI Material Safety Data Sheet.

Disposal of product residues

Do not empty product/residues of material into drains, bodies of water or ground. Cured material residues can be disposed of as construction or industrial

waste. Non-cured material residues with or without packaging must be disposed of in accordance with the local waste disposal regulations.



PCI Augsburg GmbH
Piccardstr. 11
86159 Augsburg
P.O.B. 10 22 47
86012 Augsburg
Germany
Tel. +49 (821) 59 01-0
Fax +49 (821) 59 01-390
www.pci-bodenleger.com

In view of widely varying site conditions and fields of application of our products this technical data sheet is meant to provide general application guidelines only. This information is based on our present knowledge and experience. The customer is not released from the obligation to conduct careful testing of suitability and possible application for the intended use. The customer is obliged to contact the technical help-line for fields of application not expressly stated in the technical data sheet under "Fields of Application". Use of the product beyond the fields of application as stated in the technical data sheet without previous consultation with PCI and possible resulting damages are in the sole responsibility of the customer. All descriptions,



drawings, photographs, data, ratios, weights a.o. stated herein can be changed without advance notice and do not represent the condition of the product as stipulated by contract. It is the sole responsibility of the recipient of our products to observe possible proprietary rights as well as existing laws and provisions. The reference of trade names of other companies is no recommendation and does not exclude the use of products of similar type. Our information only describe the quality of our products and services and are no warranty. Liability is accepted for incomplete or incorrect particulars in our data sheets only in the event of intent or gross negligence, without prejudice to claims under product liability laws. All transactions are subject to our Terms of Sale and Supply.

Technical Data Sheet Nr. 62, Any subsequent publication supersedes this edition.
Edition March 2014; the latest edition is always available on the Internet under www.pci-bodenleger.com