

DECLARATION OF PERFORMANCE

DE0100/03

PCI[®]
Für Bau-Profis

Augsburg, 08.10.2019

Unique identification code of the product-type:

PCI Seccoral® 1K (DE0100/03)

Intended use/es:

EN 14891 CM O1P

**Liquid-applied water impermeable product for installations beneath ceramic tiling
(bonded with PCI C2, C2F or R2 adhesives in accordance with EN 12004)**

Manufacturer:

PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg

System/s of AVCP:

System 3

Harmonised standard / Notified body/ies:

EN 14891:2012 + AC:2012

Säurefliesner-Vereinigung e. V. Institut für Wand- und Bodenbeläge (NB 1212)

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	≥ 0,5 MPa	System 3	EN 14891:2012 + AC:2012
Tensile adhesion strength after water contact	≥ 0,5 MPa		
Tensile adhesion strength after heat ageing	≥ 0,5 MPa		
Tensile adhesion strength after contact with lime water	≥ 0,5 MPa		
Crack bridging ability at low temperature	≥ 0,75 mm at -5 °C		
Waterproofing	No penetration		
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 MPa		
Dangerous substances	Comply with 4.2 (EN 14891)		

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Marc C. Köppe
managing director



Frank Rösiger
managing director